

BANANA SIZER HSR M SERIES

SIZE

High performances in reduced dimensions!

The banana sizers, HSR M series, are the result of several experiences on high speed screens (banana screens) and on statistic sizers (CVRS series). The advantages are: the increase of capacity with this sizer compared to a traditional Banana screen with the same screening surface and the improvement of cut precision compared to a traditional sizer.

RUNNING PRINCIPLE

This principle is divided in two sectors: the upper one is composed of single wire-nettings for each screening deck for material roughing; the lower sector is composed of two series-nettings with different inclination for each screening deck for material finishing

OPERATION

The operation is by means of two counter-rotating eccentric-weights motors.

CAPACITY

Capacity from 2 to 5 times higher compared to a traditional screen and with the same screening surface. The clogging of wire-nettings is reduced even with damp materials.



The sizers are suitable for a max. size of 70-80 mm and for separations from 2 to 35 mm

MAINTENANCE

Easy maintenance of sizers and quick accessibility of screening decks which may be replaced independently from the others.

EXECUTIONS

The sizers are produced in open or dusttight-closed execution.






Advantages:

- High production capacity
- # High degree of precision
- © Compact dimensions
- Low running costs
- Non-clogging of the selection deck
- Suitable for special works in the mining segments
- Dusttight closed execution, if required
- Easy and quick maintenance

For all our vibrating machines, we recommend the use of our electric units for the operating, braking in d.c. and operation control and synchronisation of motors.



The execution of banana sizers and, therefore, the dimensions of same will change according to the particular use which they are studied and planned for.

